


AC 2250

Cummins
Stamford
D+ &



ISO8528

SZUTEST

CE

2000/14/EC

&\$\$S#(#

z) \$ z'z' D:

	"	"	"	"	Amp
400/230	2250,00	1800,00	2000,00	1600,00	2886,00

Standard Specifications

z

fl ! E

z

ALTERNATOR

fl

fl " E

fl \$\$\$ \$\$\$ E

fl " \$ E

TRANSFER SWITCH

AC 2250

Cummins
Stamford
D+' &''

Manufacturer		Cummins		
Model		QSK 60 G4		
		% \$ \$ ' "# "		
		% % ' "		
		Ø) * +< DQ		
	L	60,20		
	"	159 x 190		
		14,5:1		
	fl # ı	"# "	1500	
	fl ı	L	280,00	
		L	682,00	
AbsorbedAirDischargeReSourceKey.Text	' # "	144,00		
	' # "	1800		
fl ' # ı	' # "	336,00		
	° C	450		
		24 V d.c.		
	Load	% \$ \$ ı	'+) ı) \$ ı
	# "	394,00	291,00	200,00

		Stamford
		PI 734 F
	Hz	50
	"	2080
7 cg'		0,80
		3
	ı ı	400/230
Temperatur		H

		ı ı		ı ı	
	"	"	"	"	L
AC 2250	15500	6000	2500	3220	2000
		ı ı		ı ı	
	"	"	"	"	L
AK 99		9000	2800	4800	2000

