

# COMBIPLUS G1100KEO

## GENMAC



Picture as a way of example only

MODEL	COMBIPLUS G1100KEO
<b>ALTERNATOR</b>	
Type	Synchronous, three phase, compund regulated with brushless
Voltage - Frequency	400/230V - 50 Hz
PRP power	8,8 kW / 11 kVA
LTP power	9,8 kW / 12,3 kVA
Power Factor	cosfi 0,8
Intensity PRP/LTP	16 / 18 A
Protection	IP 23
<b>ENGINE</b>	
Type	Twin -Cylinder, 4 Strokes, air cooled, 3000 rpm
Brand	KOHLER
Model	KD425/2
Displacement - HP	851 cc / 15,6
Fuel	DIESEL
Autonomy	8 h / 19 lt.
Starting System	<b>ELECTRICAL (battery included)</b>
Control Panel	1x CEE 16A 230V, 1x CEE 16A 400V; Thermal breaker, Circuit Breaker, Voltmeter (analogic), Analogic hourmeter h, Start/Stop switch, Emergency stop button, Low oil presure protection, High temperature protection.
Dimensions mm LxLxA	870x620x690
Weight - Kgs.	173
Noise Level @7m.	n.a.

[www.genmac.it](http://www.genmac.it)